

FUSO
CANTER
FG 4 x 4



**DRIVE IT
EVERYWHERE**




3.9L 4D34 ENGINE

Built for the long run.
Reliable performance
comes hand in hand
with power and fuel
efficiency.





ANTI-LOCK BRAKING SYSTEM (ABS) and Automatic Brake Adjustor



ABS help to maintain control of the vehicle during emergency braking situations, and enable proper steering around obstacles.

IN DASH GEARSHIFT





INTERIOR



01 Simple, compact & functional dashboard. Ergonomic arrangement of switchers, levers and open storage space.



02 Convenient at your finger tips.



03 New stylish and easy-to-read instrument cluster.




04 New seat design with w seat adjustment to prov comfortable driving pos

EXTERIOR



07 Headlamp levelling provide



08 Reverse sensor for easv



09 Side marker lamn




10 FISH




side
side
ition.

05 Impact absorption steering column.

06 Central locking and power window.



RISE Body with door impact



11 Maximum Gradeability

TECHNICAL SPECIFICATION



MODEL R.H.D

FG83PE6SRDG3

| WEIGHT | | | |
|---------------------------------|--------------|----|--|
| Max G.V.W. | kg | | 5,000 |
| Front axle | kg | | 1,785 |
| Rear axle | kg | | 785 |
| Kerb weight approx. | kg | | 2,570 |
| DIMENSIONS | | | |
| Wheelbase (W.B.) | mm | | 3,460 |
| Overall length (O.A.L.) | mm | | 6,105 |
| Overall width (O.A.W.) | mm | | 2,035 |
| Overall height (O.A.H.) | mm | | 2,435 |
| Tread | Front (T.F.) | mm | 1,665 |
| | Rear (T.R.) | mm | 1,560 |
| Ground clearance approx. (G.C.) | mm | | 210 |
| Cab to rear axle (C.A.) | mm | | 2,920 |
| Cab to end frame (C.E.) | mm | | 4,395 |
| Frame width (F.W.) | mm | | 750 |
| Front overhang (F.O.H.) | mm | | 1,130 |
| Rear overhang (R.O.H.) | mm | | 1,475 |
| ENGINE | | | |
| Model | - | | Mitsubishi 4D34-2AT5 turbocharge with intercooler |
| Type | - | | 4-stroke, water-cooled, direct injection diesel engine |
| No. of cylinders | - | | 4 in line |
| Piston displacement | cc | | 3,908 |
| Max. output | kW(PS)@rpm | | 81(110)@2,900 |
| Max. torque | Nm@rpm | | 275@1,600 |
| Air cleaner | - | | Dry paper element type |
| Alternator | Volt | | 24V - 50Amps |
| DRIVELINE | | | |
| Clutch | Type | | Hydraulic control, single dry plate |
| | mm | | 275 |
| Transmission | - | | M035S5 5 forward and 1 reverse speed, manual, overdrive 2nd to 5th range; Synchronmesh gears 1st & Rev. range; Constantmesh gears |
| Gear ratios | - | | 5.38-3.028-1.700-1.00-0.722-Reverse 5.380 |
| Final reduction gear | - | | Single reduction, hypoid gear |
| Ratio | - | | 6.166 |
| Transfer Case Ratio | - | | Low: 1.987, High: 1.090 |
| CABIN | | | |
| Seating capacity | - | | 3 |
| Cabin tilt | - | | Mechanical |
| Power windows | - | | Equipped |
| Central lock & alarm system | - | | Equipped |
| Reverse sensors & buzzer | - | | Equipped |
| Kangaroo bar | - | | Equipped |
| CHASSIS | | | |
| Axle type/Rating | Front | | Full floating type |
| | Rear | | Full floating type |
| Tyres | Studs | | 6 |
| | Tyre Size | | 7.5R16 |
| Steering | - | | Right hand steering. Ball nut type with integral type hydraulic power booster. Telescopic and tilt steering column with steering lock |
| Suspension | Front | | Laminated leaf springs with shock absorbers |
| | Rear | | Main and auxiliary laminated leaf springs with shock absorbers |
| Brake | Service | | Hydraulic with vacuum servo assistance, dual circuit with antilock brake system (ABS) & auto brake shoes adjuster |
| | Parking | | Internal expanding type on propeller shaft |
| | Auxiliary | | Exhaust brake |
| Fuel tank | - | | 100 liters |
| Electrical system | - | | 12 Volt x 2, 65Ah at 20 hr. rate |

FUSO authorized dealer:

40,000km
OR
2 YEARS WARRANTY*
FG 4 x 4

FREE
maintenance service**
3
TIMES

R^{24/7} ADSIDE
FUSO ASSISTANCE

FUSO Authorized Distributor:
Hap Seng Trucks Distribution Sdn Bhd (1250643-T)
No. 1, Jalan Kinrara 2